



Liquid Nitrogen Generator Specification Sheet LN260

Liquid Nitrogen Production Rate:	260 litres/day (10.8 litres/hr)
Skid Dimensions:	2.5m (L) x 2.3m (W) x 1.5m (H)
Skid Weight:	1,700 Kg
Dewar Volume:	500 Litres (132 gallons)
Cold Head Assembly:	4 x CH-110
Helium Compressor:	4 x F70H (high voltage) / F70L (low voltage) – water cooled
Electrical Input options:	480v / 3ph - 60Hz or 380v/400v/415v / 3ph - 50Hz 200v / 3ph – 50/60Hz
Power Consumption:	30kw @ 50Hz / 36kw @ 60Hz
Water Cooling Requirement:	30kw of cooling power @ 25°C
Ambient Temperature Range:	+4°C to +50°C
Maximum altitude:	10,000 feet (3,000 metres) – higher altitudes available
Nitrogen Gas Requirement:	120 LPM / <1% Oxygen (model MNG106L supplied)
Compressed Air Requirement:	Kaesar SX6 (4kw) or equivalent – 0.48m ³ /min @ 10 bar
Noise Level:	<65dBA @ 1 metre
Control System:	HMI colour graphic touch screen
Tank Level high / low Setting:	Adjustable – 0 – 100%
Main Features:	Dewar Vacuum Protection System 25%, 50%, 75%, 100% production control
Certification:	Dewar – EN 13458 / 97/23/EC; System – CE / ISO9001:2008

